


Glasstex[®] P200 Paving Composite Product Specification

Glasstex[®] P200 is used for both the reinforcement of asphalt layers in the construction of new pavements and of asphalt overlays in the rehabilitation of existing pavements.

Glasstex[®] P200 is a composite consisting of bundles of glass filaments stitched onto a polypropylene paving fabric in both the longitudinal and transverse directions using polyester (PET) yarn. The glass fibres provide high tensile stiffness, and the polypropylene fabric provides a means of maintaining the required geometry of the composite, as well as a fixing layer during installation. Once installed and saturated with bitumen, the paving fabric then acts as a waterproofing layer.



Glasstex [®] P200 Composite			
Roll width	m	1 & 2	
Roll length	m	100	
Unit weight	kg/m ²	0.67	
Roll weight	kg	72 & 144	
Glass filament content	tex/m	48 × 10 ⁴	
Glass filament mesh pitch	mm	40 × 40	
Index strength (1)	kN/m	200.0	
Maximum strain at failure (1)	%	3.0	
Paving fabric properties			
Polymer (2)		PP	
Grab tensile strength (3)	N	450.0	
Approx strain at failure (3)	%	50.0	
Asphalt retention (4)	l/m ²	1.1	

(1) Index property based on testing the individual glass filaments in accordance with BS EN ISO 3341:2000.

(2) PP denotes polypropylene.

(3) Mean value determined in accordance with ASTM D 4632.

(4) Mean value determined in accordance with ASTM D 6140.

(5) Glasstex[®] P200 is manufactured in accordance with a Quality Management System which complies with the requirements of BS EN ISO 9001:2000.

(6) All quoted dimensions and values are typical unless stated otherwise.

Determination of the suitability of any information or material for the use contemplated or the manner of use is the sole responsibility of the user.

Tensar is a registered trade mark

Tensar International Limited

Tel: +44 (0) 1254 262431
 Fax: +44 (0) 1254 266867
 E-mail: sales@tensar.co.uk
www.tensar-international.com

UK Head Office
Cunningham Court
Shadsworth Business Park
Blackburn
BB1 2QX
United Kingdom



Q 05288
ISO 9001:2008



EMS 86463
ISO 14001:2004