

Tensar Glasstex[®]Patch

Tensar Glasstex[®]Patch is used to reinforce asphalt layers in new pavement construction and in the rehabilitation of existing pavements. These products are widely used for detail repair applications, for discrete cracks, or localized areas where it is not practical to mobilize for a full width interlayer installation. These products are also used in applications where the reflective cracking is known to be beyond the capability of conventional interlayers. Both products provide a stress relief and a water barrier effect due to the continuous interface of the bitumen membrane and a reinforcement mechanism provided by the glass filaments.

Tensar Glasstex[®]Patch 660 and 880 are high strain performance mastic interlayers consisting of a coated glass yarn grid and a glass fabric integrated in a bitumen membrane, which is typically treated with quartz sand to allow for essential construction traffic after installation. The self-adhesive underside, which is protected with a peel-off film for handling, allows it to bond to the supporting pavement surface.



PROPERTY	UNIT	Glasstex[®]Patch XXXX660XXXX	Glasstex[®]Patch 880
Roll width	m	X	1
Roll length	m	15	15
Rolls on pallet	pcs	20	20
Thickness	mm	2,2	2,2
Mesh Geometry	mm	12,5 x 12,5	12.5 x 12.5
Unit Weight	g/m ²	≥1800	≥2000
Unit Weight quartz sand	g/m ²	≥150	≥150
Tensile strength MC/CMD (EN ISO 10319)	kN/m	70/110	70/110
Elongation at break MD/CMD (EN ISO 10319)	%	≤3	≤3

All quoted dimensions and values are typical and may vary from those indicated unless stated otherwise.

The information in this document supersedes any and all prior Technical Notes for the product(s) designated above, is of an illustrative nature and supplied by Tensar International Limited free of charge for general information purposes only. Tensar reserves the right to amend product descriptions, properties and specifications at any time and without prior notice. This document does not form part of any contract or intended contract. Tensar International Limited excludes to the fullest extent lawfully permitted any and all liability whatsoever for any loss or damage howsoever arising out of the use of and reliance upon this information. It is your sole responsibility and you must assume all risk and liability for the final determination as to the suitability of any Tensar International Limited product and/or design for the use and in the manner contemplated by you in connection with a particular project.

Tensar and TriAx are registered trademarks

Copyright © Tensar International Limited 2017

Tensar International Limited
Tel: **+44 (0) 1254 262431**
Fax: **+44 (0) 1254 266867**
E-mail: **sales@tensar.co.uk**
www.tensar-international.com

UK Head Office
Units 2 - 4 Cunningham Court
Shadsworth Business Park
Blackburn
BB1 2QX
United Kingdom

